

Technical Data Sheet – JustTeak™ System

Description

A PREMIUM MARINE GRADE TEAK MAINTENANCE SYSTEM used to renew and maintain the new and natural look of Teak. JustTeak Teak Cleaner removes stains, greying and old coatings whilst being gentle on teak. JustTeak Teak Brightener removes light stains, greying and brightens teak when used in combination with Teak Cleaner. JustTeak Teak Sealer provides protection from sun, rain and stains, whilst maintaining a beautiful, natural finish.

Coverage

Teak Cleaner: 5m²(54ft²) per litre
 Teak Brightener: 5m²(54ft²) per litre
 Teak Sealer (2 Coats): 5.5m²(60ft²) per litre

NOTE: Coverage is approximate as it depends on the absorbency of the Teak.

Technical Data: Teak Cleaner Part 1

Appearance & Odour Transparent Red Liquid, No Odour
 Base Water
 Specific gravity 1.056
 Boiling point 100 °C
 Thinner / Cleaner up Water
 MARPOL Compliant# Yes

Technical Data: Teak Brightener Part 2

Appearance & Odour Translucent Green Liquid, Mild Odour
 Base Water
 Specific gravity 1.008
 Boiling point 100 °C
 Thinner / Clean up Water
 MARPOL Compliant# Yes

Technical Data: Teak Sealer

Appearance & Odour Beige Opaque Liquid, Hydrocarbon Odour
 Specific gravity 0.91
 Thinner Do NOT Thin
 Clean up White Spirits or xylene
 Volatile Organic Compounds (theoretical - as packaged) 754 g/L
 Flashpoint 38-50°C (Solvent)
 Touch Dry at 23°C (73°F) 15-30 minutes
 Recoat at 23°C (73°F) Once touch dry

Miscellaneous Product Information

The touch dry and recoat time will be considerably shortened if the deck being coated is exposed to wind and/or direct sunlight

Do not allow Teak Cleaner or Teak Brightener to freeze. Store above 5°C (41°F)

#The JustTeak™ Cleaner and Brightener meets the 2018 Guidelines within Annex V of MARPOL (International Convention for the Prevention of Pollution from Ships): Cleaning agents and additives in deck and external surfaces wash water. Non-hazardous to the marine environment.

Method Statement – Just Teak™ System

Application of the Part 1 Teak Cleaner & Part 2 Teak Brightener

Preparation

Protect surfaces being cleaned that could be damaged, such as polished metal, especially aluminium. Ensure easy access to a water supply.

Application

Part 1 Teak Cleaner

1. Hose down entire area with water.
2. Ensure the teak does not dry during the cleaning process.
3. Applying the Teak Cleaner with a soft polypropylene cleaning pad, gently scrub the product across the grain of the teak. The teak will turn dark brown and the cleaning pad will fill with dirt.
4. Apply to one area at a time then immediately rinse down entire area with water to remove the cleaner. Repeat if necessary.

Part 2 Teak Brightener

1. Following the application of Part 1: Teak Cleaner.
2. Hose down entire area with water.
3. Ensure the teak does not dry during the cleaning process.
4. Apply Teak Brightener with a soft polypropylene cleaning pad, gently scrubbing across the grain of the teak. The teak will immediately lighten.
5. Apply to one area at a time then immediately rinse down entire area with water to remove the Teak Brightener. Repeat if necessary.

Application of the JustTeak Teak Sealer

Preparation

1. For freshly sanded teak: Ensure teak is clean of dust and dirt before application.
2. Weathered and previously coated teak: Clean with JustTeak Teak Cleaner and Teak Brightener to remove previous coatings, dirt and deposits that have turned teak grey, and restore natural colour.
3. Allow teak to dry thoroughly before applying Teak Sealer.

Application

1. For best results apply in temperatures above 10°C (50°F) on a sunny, low humidity day, ensuring the teak is dry. Shake vigorously prior to use. This product must be shaken periodically whilst using to ensure even colouring.
2. Apply the sealer by either brush, pad applicator or rag. Take note to apply sealer along the length of the board to ensure even coating and avoid line marks.
3. Apply generously. Allow to dry, soak up any areas that may have not absorbed the sealer. When touch dry, apply 1-2 subsequent coats until the teak stops absorbing the sealer.

LOOKING AFTER YOUR SEALED TEAK Over time the sealer will start to lose its lustre and water beading capability. A fresh coat of JustTeak: Teak Sealer should be applied to restore the finish. For best results remove the Teak Sealer with JustTeak Cleaner and Brightener and re-apply.

Cleanup

JustTeak Teak Cleaner & Brightener: Clean application equipment and surrounding areas with fresh water immediately after use.

JustTeak Teak Sealer: Clean application equipment immediately after use with white spirits or xylene. Any spills can be cleaned up using a rag soaked in white spirits.

Thoroughly review product label and Safety Data Sheet (SDS) for safety and cautions prior to using this product. Follow manufacturer's safety recommendations when using any solvent.

Disclaimer

While every precaution is taken to ensure that all information furnished in this method statement is as accurate, complete, and useful as possible, Greencorp Marine cannot assume responsibility nor incur any obligation resulting from the use of any materials, coatings, or methods specified herein.

This method statement does not attempt to address problems concerning safety associated with its use. The user of this method statement, as well as the user of all products or practices described herein, is responsible for instituting appropriate health and safety practices and for ensuring compliance with all governmental regulations.